INDUSTRIAL COMPONENT DATA

TC-D37SUB-AIO16-M-PS-UNI 2902934 PHOENIX CONTACT Module carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: TC-D37SUB-AIO16-M-PS-UNI

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	TC-D37SUB-AIO16-M-PS-UNI
Catalog number	2902934
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-54249762B3
Generated	2026-11-18

Product Overview

Module carrier
Universal termination carrier for connecting 16 MINI Analog separation amplifiers to digital or analogue input/output cards, via D-SUB plug-in connectors, 37 poles (1:1 connection), with HART-Multiplexer connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2902934
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 166 (C-5-2017)
GTIN 4046356697798
Weight per Piece (excluding packing) 1,190.100 g
Custom tariff number 85366990
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
General
Nominal voltage UN < 30 V DC (Per signal/channel)

Max. permissible current 23 mA (Signal/channel)
Degree of protection IP00
Supply
Designation Power module
Note Power supply via 2902958 MINI MCR-SL-PTB-FM power terminal and 2902961 MINI MCR-SL-FM-RC-NC error signaling module.
Input voltage 24 V DC
Input voltage range 19.2 V DC ... 30 V DC
Input current <= 2 A
Redundant supply yes, decoupled from diodes
Polarization and surge protection Yes
Output name Switching output
Contact type 1 N/C contact (alarm = open)
Maximum switching voltage 30 V DC (50 mA)
Fuse 2x 2.5 A on PCB, slow-blow (replaceable)
Status display 2 x red LED (error)
2x green LEDs (PWR1 and PWR2)
Connection 1
Connection name Power supply
Connection method Screw connection
Stripping length 7 mm
Number of connections 1
Number of positions 6
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
Connection 3
Connection name X11
Connection method ID...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TC-D37SUB-AIO16-M-PS-UNI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.