
INDUSTRIAL COMPONENT DATA

UP 4-5CT 3208722 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: UP 4-5CT



Manufacturer	PHOENIX CONTACT
MPN / Reference	UP 4-5CT
Catalog number	3208722
Category	Test plug for terminal blocks
Minimum order	10 Pcs
Document ID	EO-23CE40FC75
Generated	2026-11-18

Product Overview

Plug
Connector for five current transformers, each with forward transformer short circuit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 3208722
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
GTIN 4055626406404
Weight per Piece (excluding packing) 101.580 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Number of positions 10
Number of levels 1
Number of connections 10
Potentials 10
Nominal cross section 6 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W
Ambient temperature (operation) -50 °C ... 100 °C
Ambient temperature (assembly) -50 °C ... 100 °C
Maximum load current 15 A
Nominal current IN 15 A
Nominal voltage UN 320 V
Open side panel No
Dimensions
Width 80.6 mm
Length 45.4 mm
Height 34.3 mm
Drill hole spacing 84.6 mm
Connection data
Connection method Screw connection
Screw thread M3
Stripping length 8 mm ... 9 mm
Tightening torque, min 0.6 Nm
Tightening torque max 0.8 Nm
Connection in acc. with standard IEC 61984
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 10
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 6 mm²
Min. AWG conductor cross section, flexible 26
Max. AWG conductor cross section, flexible 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Condu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UP 4-5CT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.