INDUSTRIAL COMPONENT DATA

URK-ND 0701082 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: URK-ND



Manufacturer	PHOENIX CONTACT
MPN / Reference	URK-ND
Catalog number	0701082
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-642FF652C7
Generated	2026-11-19

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 800 V, nominal current: 76 A, connection type: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 16 mm², AWG: 20 - 6, width: 10.2 mm, colour: grey, mounting class: NS 35/7.5, NS 35/15, NS 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 0701082
Packing unit 50 pc
Catalog page Page 295 (CL-2005)
GTIN 4017918003593
Weight per Piece (excluding packing) 30.980 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of levels 1
Number of connections 2
Color gray

Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 76 A
Maximum load current 76 A (with 16 mm² conductor cross section)
Nominal voltage UN 800 V
Open side panel Yes
Dimensions
Length 64 mm
Width 10.2 mm
Height NS 35/7,5 43.5 mm
Height NS 35/15 51 mm
Height NS 32 48.5 mm
Connection data
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 10 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 6
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 6 mm²
2 conductors with same cross section, solid min. 0.5 mm²
2 conductors with same cross section, solid max. 4 mm²
2 conductors with same cross section, stranded min. 0.5 mm²
2 conductors w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / URK-ND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.