INDUSTRIAL COMPONENT DATA

URK-ND 2 0701095 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: URK-ND 2



Manufacturer	PHOENIX CONTACT
MPN / Reference	URK-ND 2
Catalog number	0701095
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-40D2BCA07D
Generated	2026-11-18

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 800 V, nominal current: 76 A, number of connections: 2, connection type: Screw connection, 1st floor, cross-section: 0.5 mm² - 16 mm², installation type: NS 35/7.5, NS 35/15, NS 32, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 0701095
Packing unit 50 pc
Catalog page Page 295 (CL-2005)
GTIN 4017918003609
Weight per Piece (excluding packing) 35.470 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of levels 1
Number of connections 2
Nominal cross section 16 mm²
Color gray

Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 2.43 W
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 76 A
Maximum load current 76 A (with 16 mm² conductor cross section)
Nominal voltage UN 800 V
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
HL 1 - HL 3
Fire protection f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / URK-ND 2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.