INDUSTRIAL COMPONENT DATA

# UT 2,5-MT RD 1132641 PHOENIX CONTACT Knife interruptible terminal block, nominal voltage: 400 V, nominal cur..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 2,5-MT RD**

PRODUCT IMAGE\nNOT AVAILABLE

| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UT 2,5-MT RD |
| Catalog number | 1132641 |
| Category | (Knife) disconnect terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-AB86BBE5E6 |
| Generated | 2026-11-18 |

## Product Overview

Knife interruptible terminal block, nominal voltage: 400 V, nominal current: 20 A, connection type: Screw connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, colour: red Interruptible terminal per blade, rated voltage: 400 V, rated current: 20 A, connection type: Screw connection, section: 0.14 mm² - 4 mm², AWG: 26 - 12, length: 57.8 mm, width: 5.2 mm, colour: yellow, mounting: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 2,5-MT RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.