INDUSTRIAL COMPONENT DATA

UT 35-FE 3047676 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 35-FE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 35-FE
Catalog number	3047676
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-6DD538D894
Generated	2026-11-18

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 1000 V, nominal current: 125 A, number of connections: 2, connection type: Screw connection, Dimensioning cross-section: 35 mm², cross-section: 1.5 mm² - 50 mm², mounting class: NS 35/7.5, NS 35/15, colour: black/yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3047676
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356762649
Weight per Piece (excluding packing) 60.730 g
Custom tariff number 85369010
Country of origin TR (Turkey)
General
Number of levels 1
Number of connections 2
Potentials 1

Nominal cross section 35 mm²
Color black/yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 4.06 W
Maximum load current 150 A (with 50 mm² conductor cross section)
Nominal current IN 125 A
Nominal voltage UN 1000 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2.2 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 1.5 mm² / 0.4 kg
35 mm² / 6.8 kg
50 mm² / 9.5 kg
Tensile test result Test passed
Conductor cross section tensile test 1.5 mm²
Tractive force setpoint 40 N
Conductor cross section tensile test 35 mm²
Tractive force setpoint 190 N
Conductor cross section ten...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 35-FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.