


INDUSTRIAL COMPONENT DATA

UT 4-HESI (5X20) GY 3074169 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-HESI (5X20) GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-HESI (5X20) GY
Catalog number	3074169
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-A32AF43544
Generated	2026-09-21

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 500 V, nominal current: 6.3 A, connection type: Screw connection, Sizing cross-section: 1 mm², cross-section: 0.14 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3074169

Packing unit 50 pc

GTIN 4046356345279

Weight per Piece (excluding packing) 17.100 g

Custom tariff number 85369095

Country of origin DE (Germany)

General

Note The current is determined by the fuse used, the voltage by the selected LED.

If the fuse is faulty, the downstream circuit will not be disconnected.

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 1.6 W

Fuse G / 5 x 20

Fuse type Glass / ceramics / ...

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)

max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)

max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)

max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)

Connection in acc. with standard IEC 60947-7-3

Maximum load current 6.3 A (the current is determined by the fuse used)

Nominal current I_N 6.3 A

Nominal voltage U_N 500 V (The voltage is determined by the fuse or selected LED display)

Open side panel No

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-HESI (5X20) GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.