INDUSTRIAL COMPONENT DATA

UT 4-L/HESILED 60 (5X20) 3214367 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-L/HESILED 60 (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-L/HESILED 60 (5X20)
Catalog number	3214367
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-E43679B2F5
Generated	2026-11-18

Product Overview

Fuse modular terminal block
Rail terminal for fuse, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 60 V, nominal current: 30 A, connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.14 mm²- 6 mm², connection type: Screw connection, Sizing cross-section: 1 mm², cross-section: 0.14 mm²- 4 mm², Mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3214367
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 232 (C-1-2017)
GTIN 4055626030784
Weight per Piece (excluding packing) 33.140 g
Custom tariff number 85369095
Country of origin PL (Poland)
General

Note The current is determined by the fuse used, the voltage by the selected LED.
If the fuse is faulty, the downstream circuit will not be disconnected.
Number of levels 2
Number of connections 4
Nominal cross section 4 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 1.6 W (the value is multiplied when connecting multiple levels)
Fuse G / 5 x 20
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)
max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)
max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)
max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)
LED voltage range 30 V AC ... 60 V AC
LED current range 0.4 mA ... 0.86 mA
Connection in acc. with standard IEC 60947-7-2/IEC 60947-7-3
Maximum load current 36 A (the current is determined by the fuse used)
Nominal current IN 30....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-L/HESILED 60 (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.