INDUSTRIAL COMPONENT DATA

UT 6-3L 3046703 PHOENIX CONTACT Multi-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 6-3L



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 6-3L
Catalog number	3046703
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-E213E181C7
Generated	2026-11-18

Product Overview

Multi-level terminal block
Multi-floor terminal block, nominal voltage: 1000 V, nominal current: 36 A, connection type: Screw connection, Dimension cross-section: 6 mm², cross-section: 0.2 mm² - 10 mm², installation type: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3046703
Packing unit 50 pc
Catalog page Page 243 (C-1-2017)
GTIN 4055626140315
Weight per Piece (excluding packing) 57.340 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 3
Number of connections 6
Nominal cross section 6 mm²
Color gray

Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 36 A
Maximum load current 50 A (with 10 mm² conductor cross section)
Nominal voltage UN 1000 V
Open side panel Yes
Number of positions 1
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2.2 kV
Checking the mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.2 kg
6 mm2/ 1.4 kg
10 mm² / 2 kg
Tensile test result Test passed
Conductor cross section tensile test 0.2 mm²
Tractive force setpoint 10 N
Conduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 6-3L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.