INDUSTRIAL COMPONENT DATA

UTI 2,5-L/LTB 3076023 PHOENIX CONTACT Installation level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTI 2,5-L/LTB



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTI 2,5-L/LTB
Catalog number	3076023
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-D717F789D3
Generated	2026-11-19

Product Overview

Installation level terminal block
Distribution floor terminal block, with integrated panel saw, nominal voltage: 400 V, nominal current: 24 A, Screw connection, 1., 2. and 3rd floor, Dimensioning cross-section: 4 mm², cross-section: 0.2 mm² - 4 mm², Dimensioning cross-section: 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey
Stage terminal block for installations, with integrated shut-off knife, nominal voltage: 400 V, nominal current: 24 A, Screwed connection, 1., 2. and 3. Stage, Reference cross-section: 4 mm2, Cross-section: 0.2 mm2 - 4 mm2, Reference cross-section: 1.5 mm2, Installation type: NS 35/7.5, NS 35/15, Colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3076023
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356958233
Weight per Piece (excluding packing) 17.650 g
Custom tariff number 85369010
Country of origin DE (Germany)

General
Number of levels 3
Number of connections 4
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current 30 A (with 4 mm² conductor cross section and 3-pos. terminal block)
16 A (Upper level)
Rated surge voltage 4 kV
6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)
Nominal current IN 24 A (with 4 mm² conductor cross section)
Maximum load current 30 A (with 4 mm² conductor cross section and 3-pos. terminal block)
Nominal voltage UN 400 V (phase conductor/phase conductor)
Nominal current IN(upper level) 16 A
Maximum load current (upper level) 16 A (with 4 mm² conductor cross section)
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTI 2,5-L/LTB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.