
INDUSTRIAL COMPONENT DATA

UTME 6-SET POWER 1 3036001 PHOENIX CONTACT Starter kit

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTME 6-SET POWER 1



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTME 6-SET POWER 1
Catalog number	3036001
Category	Installation clamp for meters
Minimum order	1 Pcs
Document ID	EO-70A39D6DDE
Generated	2026-11-19

Product Overview

Starter kit
Beginner's kit consisting of measuring transducer disconnector terminals in quick-connect technology, marking material, bridging and test accessories. A terminal strip can be individually mounted for three-phase transformer switching (current and voltage).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3036001
Packing unit 1 pc
GTIN 4055626345451
Weight per Piece (excluding packing) 99.990 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Note Quantity specifications on the set contents under downloads
Set consists of 3047400 UTME 6
3047413 UTMED 6
3047442 UTMED 6-PE

3047426 D-UTME 6
0311139 ATP-URTK/SP
3034387 CARRIER 35-8
3034468 SB-ME 2-8
3030284 FBS 2-8
3032745 PAI-4-FIX YE
3032758 PAI-4-FIX GN
3032761 PAI-4-FIX VT
3032729 PAI-4-FIX BU
3034439 S-ME 6
3022276 CLIPFIX 35-5
0811969 KLM 3
0818072 UC-TM 8
Dimensions
Width 225 mm
Length 315 mm
Height 65 mm
Connection data
Connection method Screw connection
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Articles in set
Test disconnect terminal block, nom. voltage: 500 V, nominal current: 30 A, connection method: Screw connection, cross section: 0.2 mm² - 10 mm², AWG: 24 - 8, length: 100.8 mm, width: 8.2 mm, color: gray, mounting: NS 35/7,5, NS 35/15, nom. voltage: 500 V
Feed-through terminal block, nom. voltage: 500 V, nominal current: 41 A, connection method: Screw connection, number of connections: 2, cross section: 0.2 mm² - 10 mm², AWG: 24 - 8, width: 8.2 mm, color: gray, mounting type: NS 35/7,5, NS 35/15
Ground modular terminal block, connection method: Screw connection, number of connections: 2, cross section...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTME 6-SET POWER 1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.