INDUSTRIAL COMPONENT DATA

# UTTB 4 WH 1237651 PHOENIX CONTACT Double-level terminal block, nominal voltage: 800 V, nominal current: 30 A..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 4 WH**

PRODUCT IMAGE\nNOT AVAILABLE

| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UTTB 4 WH |
| Catalog number | 1237651 |
| Category | Feed-through terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-EDC0766F89 |
| Generated | 2026-11-18 |

## Product Overview

Double-level terminal block, nominal voltage: 800 V, nominal current: 30 A, connection type: Screw connection, 1st and 2nd floor, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: white
Double-decker terminal, connection type: Screw connection, section: 0.14 mm² - 6 mm², AWG: 26 - 10, width: 6.2 mm, color: white, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 4 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.