INDUSTRIAL COMPONENT DATA

PLC-V8/D15B/OUT 2296061 PHOENIX CONTACT System connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-V8/D15B/OUT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-V8/D15B/OUT
Catalog number	2296061
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-DFF8CD0F49
Generated	2026-11-18

Product Overview

System connection
V8 adapter for 8 x PLC-INTERFACE (6.2 mm), control: PLC wiring system for output cards, connection 1: Screw connection 1x, connection 2: D-SUB connection female 1x 15-poles, connection 3: Plug-in connection (Fits into 8x PLC-INTERFACE terminals), number of channels: 8, control logic: plusschaltend

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2296061
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 425 (C-5-2017)
GTIN 4017918189112
Weight per Piece (excluding packing) 39.100 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 50 mm
Height 39 mm

Depth 50 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
General
Max. perm. operating voltage 30 V DC
Max. perm. current (per branch) 1 A (per signal path)
Max. permissible current (separate power supply) 3 A
Number of positions 15
Status display Green LED
Mounting position any
Degree of protection IP20
Connection data for connection 1
Connection name Supply
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Number of connections 1
Connection data for connection 2
Connection name Controller level
Connection method D-SUB socket strip
Number of connections 1
Number of positions 15
Connection data for connection 3
Connection name Field level
Connection method Plug connection
Note Can be snapped onto 8x PLC-INTERFACE terminals
Supported controller
Controller HONEYWELL Experion PKS C300/C-Series
- suitable I/O card TDOB01 (non-redundant)
TDOB11 (redundant)
Standards and Regulations
Connection in acc. with standard CUL
Sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-V8/D15B/OUT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.