INDUSTRIAL COMPONENT DATA

PLC-V8/FLK14/OUT 2295554 PHOENIX CONTACT System connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-V8/FLK14/OUT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-V8/FLK14/OUT
Catalog number	2295554
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-D9AB82FF32
Generated	2026-11-18

Product Overview

System connection
V8 adapter for 8 x PLC-INTERFACE (6.2 mm), control: PLC wiring system for output cards, connection 1: Screw connection 1x, connection 2: IDC/FLK male connector 1x 14-poles, connection 3: Plug-in connection (Fits into 8x PLC-INTERFACE terminals), number of channels: 8, control logic: plusschaltend
V8 adapter for 8 x PLC-INTERFACE (6.2 mm), controller: PLC system cabling of output cards, connection 1: IDC/FLK pin strip 1x 14-position, connection 2: Plug-in connection (Can be snapped onto 8x PLC-INTERFACE terminals), connection 3: Screw connection 1x 2-position, number of channels: 8, control logic: positive switching

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Interface module
Product family PLC-INTERFACE
Number of positions 14
No. of channels 8
Data management status
Article revision 13
Insulation characteristics: Air clearances and creepage distances
Insulation Functional insulation
Overvoltage category II

Pollution degree 2
Electrical propertiesOperating voltage range 18 V DC ... 33.6 V DC
Current (per branch) <= 1 A
Current (Power supply) <= 3 A
Air clearances and creepage distances
Rated insulation voltage 50 V
Rated surge voltage 0.5 kV (1.2/50 us)
Supported controller SIEMENS S7-1500
Suitable I/O card 6ES7522-1BH00-0AB0
6ES7522-1BH01-0AB0
6ES7522-1BL00-0AB0
6ES7522-1BL01-0AB0
Supported controller SIEMENS S7-400
Suitable I/O card 6ES7422-1BL00-0AA0
6ES7422-7BL00-0AB0
Supported controller ALLEN-BRADLEY ControlLogix
Suitable I/O card 1756-OB32
1756-OB16E
Supported controller ALLEN-BRADLEY PLC 5
Suitable I/O card 1771 OBN
Supported controller ALLEN-BRADLEY SLC 500
Suitable I/O card 1746 OB 32
Supported controller HONEYWELL Experion PKS C200
Suitable I/O card TC-ODD 321
Supported controller MITSUBISHI MELSEC Q
Suitable I/O card QY81P
QY82P
Supported controller SIEMENS S7-300 / ET 200 M
Suitable I/O card CPU 313C-2DP
CPU 314C-2DP
CPU 314C-2PtP
6ES7322-1BH01-0AA0
6ES7322-1BL00-0AA0
6ES7323-1BH01-0AA0
6ES7323-1BL00-0AA0
CPU 313C
CPU 313C-2PtP
Supported controller ABB S800 I/O
Suitable I/O card DO810
DO840
Supported controller EMERSON DeltaV
Suitable I/O card VE4002S1T1B3
VE4002S1T2B3
VE400...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-V8/FLK14/OUT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.