INDUSTRIAL COMPONENT DATA

VAL-MS-T1/T2 3+1-BE/FM/10 1065864 PHOENIX CONTACT Type 2 surge protection base element

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS-T1/T2 3+1-BE/FM/10



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS-T1/T2 3+1-BE/FM/10
Catalog number	1065864
Category	Basic element for surge protection device
Minimum order	10 Pcs
Document ID	EO-D1D9688932
Generated	2026-11-18

Product Overview

Type 2 surge protection base element
Base element for type 2 unloaders from the VALVETRAB MS product series, with remote indication contact. Execution for three-phase power supplies with separate N and PE conduction.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 1065864
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
GTIN 4055626730165
Weight per Piece (excluding packing) 251.890 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Height 98.7 mm
Width 71 mm
Depth 51.5 mm (incl. DIN rail 7.5 mm)

Horizontal pitch 4 Div.
Ambient conditions
Degree of protection IP20 (only when all terminal points are used)
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 30g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 7.5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification II
T2
EN type T2
Mounting type DIN rail: 35 mm
Color jet black RAL 9005
Housing material PBT
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type Base element, DIN rail mounting
Number of positions 4
Surge protection fault message Optical, remote indicator contact
Protective circuit
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous voltage UC 500 V AC
Rated load current IL 80 A
Short-circuit current rating ISCCR 25 kA
Max. backup fuse with V-type through wiring 80 A (gG)
Max. backup fuse with branch wiring 125 A (gG)
Indicator/remote signaling
Switching function PDT contact
Operating voltage 5 V AC ... 250 V AC
30 V DC
Operating current 5 mA AC ... 750 mA AC
1 A DC
Connection method P...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS-T1/T2 3+1-BE/FM/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.