INDUSTRIAL COMPONENT DATA

VAL-US-120/65/1+0-FM 2910355 PHOENIX CONTACT Type 1/2 surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-US-120/65/1+0-FM



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-US-120/65/1+0-FM
Catalog number	2910355
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-76B787F32F
Generated	2026-11-19

Product Overview

Type 1/2 surge protection device
1-channel surge protection device with remote indication contact, for 120 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2910355
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626444956
Weight per Piece (excluding packing) 150.000 g
Custom tariff number 85363030
Country of origin US (United States)
Dimensions
Height 96.8 mm
Width 17.8 mm
Depth 77.5 mm
Horizontal pitch 1 Div.
Ambient conditions

Degree of protection IP20 (only when all terminal points are used)
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 30g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 7.5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification I / II
T1 / T2
EN type T1 / T2
IEC power supply system TN-C
Mode of protection L-PEN
Mounting type DIN rail: 35 mm
Color jet black RAL 9005
Housing material PA 6.6
PBT
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type DIN rail module, two-section, divisible
Number of positions 1
Surge protection fault message Optical, remote indicator contact
Protective circuit
Nominal voltage UN 120 V AC (TN-C)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous operating voltage UC(L-PEN) 175 V AC
Rated load current IL 80 A
Residual current IPE <= 0.8 mA
Nominal discharge current In(8/20) µs 20 kA
Maximum discharge current Imax(8/20) µs 65 kA
Total discharge current Itotal(10/350) µs 12.5 kA
Short-circuit current rating ISCCR 25 kA
Voltage prot...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-US-120/65/1+0-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.