INDUSTRIAL COMPONENT DATA

VAL-US-48/40-P 2910333 PHOENIX CONTACT Type 2 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-US-48/40-P



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-US-48/40-P
Catalog number	2910333
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	1 Pcs
Document ID	EO-DE8C4D0364
Generated	2026-11-18

Product Overview

Type 2 surge protection plug
Type 2 surge protection device, UL recognized component, IEC type 2 plug-in surge protection with varistor and thermal disconnect device for use with VAL-US base elements, mechanical and optical fault signaling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2910333
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626444468
Weight per Piece (excluding packing) 29.000 g
Custom tariff number 85363030
Country of origin US (United States)
Dimensions
Height 52.4 mm
Width 17.5 mm
Depth 55.3 mm
Horizontal pitch 1 Div.

Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification II
T2
EN type T2
IEC power supply system DC
Mode of protection L-N
L-PEN
N-PE
Mounting type on base element
Color jet black RAL 9005
Housing material PA 6.6
PBT
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type Male
Number of positions 1
Surge protection fault message optical
Protective circuit
Nominal voltage UN 60 V DC ±10 %
-48 V DC ±10 % (RRH)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous voltage UC 100 V DC
Residual current IPE <= 450 µA
Standby power consumption PC <= 35 mVA
Nominal discharge current In(8/20) µs 15 kA
Maximum discharge current Imax(8/20) µs 40 kA
Short-circuit current rating ISCCR 25 kA
Voltage protection level Up <= 0.55 kV
Residual voltage Ures <= 0.55 kV (at In)
<= 0.425 kV (at 10 kA)
<= 0.325 kV (at 5 kA)
<= 0.275 kV (at 3 kA)
TOV behavior at UT....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-US-48/40-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.