

INDUSTRIAL COMPONENT DATA

SACC-V-3CON-M16/A-1L-S 1544714 PHOENIX CONTACT

Valve connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-V-3CON-M16/A-1L-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-V-3CON-M16/A-1L-S
Catalog number	1544714
Category	Valve connector (field assembly)
Minimum order	1 Pcs
Document ID	EO-4F93B29C2F
Generated	2026-09-21

Product Overview

Valve connectors

Valve Connector, Universal, 3-Pole, Valve Connector A, Screw Connection, M16 Cable Gland, Cable Outer Diameter 5 mm ... 10 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data

Orderkey 1544714

Packing unit 1 pc

Catalog page Page 27 (C-2-2017)

GTIN 4046356116381

Weight per Piece (excluding packing) 36.330 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

External diameter 5 mm ... 10 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 60 °C (valve plug)

Degree of protection IP65

General

Rated current at 40°C 4 A

Rated voltage 24 V

Number of positions 3

Insulation resistance > 2 G?

Standards/regulations Valve connector EN 175301-803

Status display Yellow LED

Protective circuit/component Z diode

Overvoltage category II

Degree of pollution 3

Connection method Screw connection

Conductor cross section 0.34 mm² ... 2.5 mm²

Conductor cross section AWG 22 ... 13

Insertion/withdrawal cycles 50 (Valve connector)

Material

Flammability rating according to UL 94 HB

Valve plug contact material CuSn

Valve plug contact surface material Ag

Valve plug contact insert material PBT

Material housing valve plug PA

Sealing material NBR

Cable

Standards/specifications Valve connector EN 175301-803

Standards and Regulations

Standard designation Valve connector

Standards/regulations EN 175301-803

Flammability rating according to UL 94 HB

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 25;

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-V-3CON-M16/A-1L-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.