INDUSTRIAL COMPONENT DATA

SACC-V-3CON-PG9/A-1L-S 1671137 PHOENIX CONTACT Valve connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-V-3CON-PG9/A-1L-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-V-3CON-PG9/A-1L-S
Catalog number	1671137
Category	Valve connector (field assembly)
Minimum order	1 Pcs
Document ID	EO-F71B7E526E
Generated	2026-11-19

Product Overview

Valve connectors
Valve Connector, Universal, 3-Pole, Valve Connector A, Screw Connection, Pg9 Cable Gland, Cable Outer Diameter 6 mm ... 8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data
Orderkey 1671137
Packing unit 1 pc
Catalog page Page 27 (C-2-2017)
GTIN 4017918134983
Weight per Piece (excluding packing) 34.600 g
Custom tariff number 85366990
Country of origin CZ (Czech Republic)
Dimensions
External diameter 6 mm ... 8 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C (valve plug)
Degree of protection IP65

General
Rated current at 40°C 4 A
Rated voltage 24 V
Number of positions 3
Insulation resistance > 2 G?
Standards/regulations Valve connector EN 175301-803
Status display Yellow LED
Protective circuit/component Z diode
Overvoltage category II
Degree of pollution 3
Connection method Screw connection
Conductor cross section 0.34 mm² ... 2.5 mm²
Conductor cross section AWG 22 ... 13
Insertion/withdrawal cycles 50 (Valve connector)
Material
Flammability rating according to UL 94 HB
Valve plug contact material CuSn
Valve plug contact surface material Ag
Valve plug contact insert material PBT
Material housing valve plug PA
Cable
Standards/specifications Valve connector EN 175301-803
Standards and Regulations
Standard designation Valve connector
Standards/regulations EN 175301-803
Flammability rating according to UL 94 HB
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127143400eCl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-V-3CON-PG9/A-1L-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.