INDUSTRIAL COMPONENT DATA

FLKM 14-PA-MODI/M340 2903208 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 14-PA-MODI/M340



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 14-PA-MODI/M340
Catalog number	2903208
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-0BCAE03C1D
Generated	2026-11-18

Product Overview

Front adapters
VARIOFACE Front Adapter for Schneider Electric Modicon M340

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Front adapter
Product family VARIOFACE
Data management status
Article revision 06
Insulation characteristics: Air clearances and creepage distances
Insulation Functional insulation
Overvoltage category II
Pollution degree 2
Electrical propertiesOperating voltage (AC) <= 30 V AC
Operating voltage (DC) <= 60 V DC
Nominal operating mode 100% operating factor
Current (per branch) <= 1 A
Current (Voltage supply via IDC/FLK) <= 3 A
Current (Voltage supply via Push-in connection) <= 10 A

Air clearances and creepage distances
Rated insulation voltage 63 V
Rated surge voltage 0.6 kV (1.2/50 us)
Supported controller SCHNEIDER ELECTRIC Modicon M340
Suitable I/O card BMX DDI 1602
BMX DDI 1603
BMX DAI 1602
BMX DAI 1603
BMX DDO 1602
BMX DDO 1612
Connection dataConnection 1 (control level)
Connection method Plug-in connection
Number of connections 2
Number of positions 10
Pitch 7.5 mm
Connection 2 (field level)
Connection in acc. with standard IEC 60603-13
Connection method IDC/FLK pin strip
Number of connections 2
Number of positions 14
Insertion/withdrawal cycles > 50
Pitch 2.54 mm
Connection 3 (supply)
Connection method Push-in spring connection
Stripping length 10 mm
Number of connections 1
Number of positions 4
Conductor cross section rigid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
0.25 mm² ... 2.5 mm² (Ferrule without plastic sleeve)
0.25 mm² ... 1 mm² (Ferrule with plastic sleeve)
Conductor cross section flexible...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 14-PA-MODI/M340 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.