INDUSTRIAL COMPONENT DATA

VIP-2/PT/FLK50 (1-40) /S7 2903804 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/PT/FLK50 (1-40) /S7



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/PT/FLK50 (1-40) /S7
Catalog number	2903804
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-5386A92476
Generated	2026-11-19

Product Overview

Passive module
VARIOFACE interconnect module for Siemens SIMATIC® S7-300, with SIMATIC-specific® marking (1-40), push-in connection, module width: 107.9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2903804
Packing unit 1 pc
Catalog page Page 508 (C-5-2017)
GTIN 4046356796514
Weight per Piece (excluding packing) 219.800 g
Custom tariff number 85366990
Country of origin US (United States)
Dimensions
Width 107.9 mm
Height 72.1 mm
Depth 56 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 60 V AC/DC
Max. perm. current (per branch) 1 A
Number of positions 50
Status display No
Mounting position any
Connection data for connection 1
Connection name Field level
Connection method Push-in connection
Stripping length 8 mm
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 26 ... 14
Connection data for connection 2
Connection name Controller level
Connection method IDC/FLK pin strip
Number of connections 1
Number of positions 50
Pitch 2.54 mm
Supported controller
Controller ALLEN-BRADLEY PLC 5
- suitable I/O card 1771 OBN
Standards and Regulations
Connection in acc. with standard CSA
Standards/regulations IEC 60664
DIN EN 50178
Rated surge voltage 0.6 kV
Degree of pollution 2
Overvoltage category II
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/PT/FLK50 (1-40) /S7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.