INDUSTRIAL COMPONENT DATA

UM 45-D37SUB/S/ZFKDS 2293640 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM 45-D37SUB/S/ZFKDS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM 45-D37SUB/S/ZFKDS
Catalog number	2293640
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-5F9F94B41B
Generated	2026-11-18

Product Overview

Interface module
VARIOFACE module, spring-loaded and subminiature plug D, for mounting on NS 35/7.5, number of poles 37

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2293640
Packing unit 1 pc
Catalog page Page 308 (IF-2011)
GTIN 4017918120542
Weight per Piece (excluding packing) 140.300 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 121 mm
Height 45 mm
Depth 50 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
60 V DC
Max. perm. current (per branch) 2.5 A
1.5 A (with even load on all branches)
Number of positions 37
Status display No
Mounting position any
Degree of protection IP20
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Spring-cage connection
Stripping length 8 mm
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 1.5 mm²
Conductor cross section AWG 24 ... 14
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
Standards and Regulations
Standards/regulations IEC 60664
DIN EN 50178
Rated insulation voltage 125 V
Rated surge voltage 1.2 kV
Insulation Functional insulation
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.12...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM 45-D37SUB/S/ZFKDS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.