
INDUSTRIAL COMPONENT DATA

UMK- PVB 2/16/ZFKDS 2302353 PHOENIX CONTACT Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-PVB 2/16/ZFKDS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMK-PVB 2/16/ZFKDS
Catalog number	2302353
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-A5CBFF6BD6
Generated	2026-11-18

Product Overview

Potential distributors
VARIOFACE module, with two potential bars (P1,P2) for potential distribution, for mounting on NS 32, or on NS 35/7,5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataNotesNotes on operation The necessary requirements for insulation (basic insulation or reinforced insulation) from adjacent modules (in DIN-rail direction) must be realized by applying suitable measures (e. g., partition plates).
Notes on operation Ensure that the supply voltage of the device has a common reference potential.
Notes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
Product propertiesProduct type Potential distributor
Product family VARIOFACE
Data management status
Article revision 07
Insulation characteristics
Insulation Functional insulation
Pollution degree 2
Electrical propertiesNominal voltage UN 250 V AC/DC

Max. current carrying capacity per branch 17 A
Max. total current of all branches 32 A (per potential)
Rated insulation voltage 260 V
Rated surge voltage 2.3 kV
Connection dataFeed-in
Connection method Spring-cage connection
Stripping length 8 mm
Number of connections 2
Conductor cross section rigid 0.2 mm² ... 6 mm²
Conductor cross section flexible 0.2 mm² ... 4 mm²
Conductor cross section AWG 24 ... 10
Distribution
Connection method Spring-cage connection
Stripping length 8 mm
Number of connections 16
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Condu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-PVB 2/16/ZFKDS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.