
INDUSTRIAL COMPONENT DATA

UMK- PVB 2/24/ZFKDS 2302366 PHOENIX CONTACT Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-PVB 2/24/ZFKDS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMK-PVB 2/24/ZFKDS
Catalog number	2302366
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-ECA8C8C367
Generated	2026-11-18

Product Overview

Potential distributors
VARIOFACE module, with two potential bars (P1,P2) for potential distribution, for mounting on NS 32, or on NS 35/7,5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2302366
Packing unit 1 pc
Catalog page Page 323 (IF-2011)
GTIN 4017918880514
Weight per Piece (excluding packing) 139.000 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 67.5 mm
Height 77 mm
Depth 52 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Nominal voltage UN 250 V AC/DC
Max. current carrying capacity per branch 17 A
Total current 32 A (per potential)
Mounting position any
Standards/regulations IEC 60664
DIN EN 50178
Rated surge voltage 2.3 kV
Rated insulation voltage 260 V
Degree of pollution 2
Overvoltage category II
Degree of protection IP20
Connection data, supply
Connection method Spring-cage connection
Stripping length 8 mm
Conductor cross section solid 0.2 mm² ... 6 mm²
Conductor cross section flexible 0.2 mm² ... 4 mm²
Conductor cross section AWG 24 ... 10
Number of connections 2
Connection data, distribution
Connection method Spring-cage connection
Stripping length 8 mm
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Number of connections 24
Standards and Regulations
Connection in acc. with standard CUL
Standards/regulations IEC 60664
DIN EN 50178
Rated insulation voltage 260 V
Rated surge voltage 2.3 kV
Insulation Functional insulation
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoH...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-PVB 2/24/ZFKDS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.