
INDUSTRIAL COMPONENT DATA

UMK-RJ45/S/8PTDA 2900682 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UMK-RJ45/S/8PTDA



Manufacturer	PHOENIX CONTACT
MPN / Reference	UMK-RJ45/S/8PTDA
Catalog number	2900682
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-BBFA5EA3F6
Generated	2026-11-18

Product Overview

Passive module
VARIOFACE module for the connection of an RJ45 female connector with spring-loaded double terminal blocks in direct connection technology.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2900682
Packing unit 1 pc
Catalog page Page 320 (IF-2011)
GTIN 4046356524353
Weight per Piece (excluding packing) 57.000 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 25 mm
Height 91 mm
Depth 51 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
50 V DC
Max. perm. current (per branch) 1 A
Max. permissible current (separate power supply) 4 A
Number of positions 8
Mounting position any
Degree of protection IP00
Connection data for connection 1
Connection name Field level
Connection method Spring-cage connection
Stripping length 8 mm
Conductor cross section solid 0.2 mm² ... 1.5 mm²
Conductor cross section flexible 0.2 mm² ... 1.5 mm²
Conductor cross section AWG 24 ... 16
Number of positions 10
Connection data for connection 2
Connection name Controller level
Connection method RJ45 socket
Number of connections 1
Number of positions 8
Standards and Regulations
Designation Air clearances and creepage distances
Standards/regulations DIN EN 50178: 1998-04
Rated insulation voltage 50 V
Rated surge voltage 0.5 kV (1.2/50 us)
Insulation Functional insulation
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UMK-RJ45/S/8PTDA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.