INDUSTRIAL COMPONENT DATA

VIP-2/SC/D37SUB/M 2900676 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/D37SUB/M



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/SC/D37SUB/M
Catalog number	2900676
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-837FDF0ACB
Generated	2026-11-18

Product Overview

Interface module
VARIOFACE module, with screw connection and D-SUB miniature male connector, for mounting on symmetrical NS 35 rails, number of poles: 37

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2900676
Packing unit 1 pc
Catalog page Page 487 (C-5-2017)
GTIN 4046356535557
Weight per Piece (excluding packing) 206.900 g
Custom tariff number 85366990
Country of origin US (United States)
Dimensions
Width 101 mm
Height 65.5 mm
Depth 45.1 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
60 V DC
Max. perm. current (per branch) 2 A
Number of positions 37
Status display No
Mounting position any
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M 3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
Supported controller
Controller HONEYWELL Experion PKS C300/C-Series
- suitable I/O card TDIL01 (non-redundant)
TDIL11 (redundant)
TDOB01 (non-redundant)
TDOB11 (redundant)
TAIX01 (non-redundant)
TAIX11 (redundant)
TAOX01 (non-redundant)
TAOX11 (redundant)
Standards and Regulations
Connection in acc. with standard CUL
Standards/regulations DIN EN 50178
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/D37SUB/M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.