INDUSTRIAL COMPONENT DATA

VIP-3/SC/FLK40 2315078 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/SC/FLK40



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-3/SC/FLK40
Catalog number	2315078
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-0C80F182B8
Generated	2026-11-18

Product Overview

Interface module
VARIOFACE module, with screw connection and plug-in flat cable connector, for mounting on symmetrical NS 35 rails, with male connector as well as short and long locking flanges for female connectors, number of poles: 40

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2315078
Packing unit 1 pc
Catalog page Page 567 (C-5-2017)
GTIN 4046356313292
Weight per Piece (excluding packing) 197.900 g
Custom tariff number 85366990
Country of origin US (United States)
Dimensions
Width 77.4 mm
Height 69 mm
Depth 62 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 60 V AC/DC
Max. perm. current (per branch) 1 A
Number of positions 40
Status display No
Mounting position any
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M 3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method IDC/FLK pin strip
Number of connections 1
Number of positions 40
Pitch 2.54 mm
Supported controller
Controller ALLEN-BRADLEY SLC 500
- suitable I/O card 1746 OB 32
1746 OV 32
1746 IB 32
1746 IV 32
Standards and Regulations
Connection in acc. with standard CSA
Standards/regulations IEC 60664
DIN EN 50178
Rated surge voltage 0.6 kV
Degree of pollution 2
Overvoltage category II
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/SC/FLK40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.