
INDUSTRIAL COMPONENT DATA

# VIP-2/PT/D15SUB/F 2903780 PHOENIX CONTACT Interface module

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/PT/D15SUB/F**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VIP-2/PT/D15SUB/F |
| Catalog number | 2903780 |
| Category | Interface module |
| Minimum order | 1 Pcs |
| Document ID | EO-B19D568CDD |
| Generated | 2026-11-18 |

## Product Overview

Interface module
VARIOFACE module, with push-in connection and D-SUB miniature connection socket, for mounting on symmetrical NS 35 rails, number of poles: 15

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Key Commercial Data
Orderkey 2903780
Packing unit 1 pc
Catalog page Page 572 (C-5-2017)
GTIN 4046356796552
Weight per Piece (excluding packing) 110.200 g
Custom tariff number 85366990
Country of origin US (United States)
Dimensions
Width 46.9 mm
Height 72.1 mm
Depth 63 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
60 V DC
Max. perm. current (per branch) 2 A
Number of positions 15
Status display No
Mounting position any
Connection data for connection 1
Connection name Field level
Connection method Push-in connection
Stripping length 8 mm
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 26 ... 14
Connection data for connection 2
Connection name Controller level
Connection method D-SUB socket strip
Number of connections 1
Number of positions 15
Standards and Regulations
Connection in acc. with standard CSA
Standards/regulations IEC 60664
DIN EN 50178
Rated surge voltage 1.2 kV
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127371000eCl@ss 6.027371000eCl@ss 7.027141152eCl@ss 8.027141152eC...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/PT/D15SUB/F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.