INDUSTRIAL COMPONENT DATA

VIP-2/PT/D37SUB/M 2904277 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/PT/D37SUB/M



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/PT/D37SUB/M
Catalog number	2904277
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-9EF0261FCD
Generated	2026-11-18

Product Overview

Interface module
VARIOFACE module, with push-in connection and D-SUB miniature male connector, for mounting on NS 35 symmetrical rails, number of poles: 37
VARIOFACE module, with push-in connection and plug D-SUB miniature pin strip, for mounting on NS 35 rails, 37-pos.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataProduct propertiesProduct type Interface module
Product family VARIOFACE Professional
Number of positions 37
No. of channels 16
Data management status
Article revision 05
Insulation characteristics
Overvoltage category II
Pollution degree 2
Electrical propertiesNominal voltage UN 25 V AC
60 V DC
Max. current carrying capacity per branch 2 A

Rated surge voltage 1.2 kV
Supported controller HONEYWELL Experion PKS C300/C-Series
Suitable I/O card TDIL01 (non-redundant)
TDIL11 (redundant)
TDOB01 (non-redundant)
TDOB11 (redundant)
TAIX01 (non-redundant)
TAIX11 (redundant)
TAOX01 (non-redundant)
TAOX11 (redundant)
Connection dataField level
Connection in acc. with standard IEC / EN
Connection method Push-in connection
Stripping length 8 mm
Number of positions 37
Conductor cross section rigid 0.14 mm² ... 4 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 26 ... 14
Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
SignalingStatus display no
Status display present No
DimensionsItem dimensions
Width 102.8 mm
Height 72.1 mm
Depth 46.6 mm
Material specificationsColor gray (RAL 7042)
Housing insulation material Polyamide PA non-reinforced
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -20 °C ... 70 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Standards and regulationsStandards/regulations IEC 60664
DIN EN 50178
MountingMounting type DI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/PT/D37SUB/M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.