INDUSTRIAL COMPONENT DATA

VIP-3/PT/PDM-2/24 2903798 PHOENIX CONTACT Potential distributors

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/PT/PDM-2/24



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-3/PT/PDM-2/24
Catalog number	2903798
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-E6677555E3
Generated	2026-11-18

Product Overview

Potential distributors
VARIOFACE module with push-in connection and two busbars (P1, P2) for potential distribution, for installation on NS 35 symmetrical rails. Module width: 57.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2903798
Packing unit 1 pc
Catalog page Page 598 (C-5-2017)
GTIN 4046356796729
Weight per Piece (excluding packing) 156.000 g
Custom tariff number 85369010
Country of origin US (United States)
Dimensions
Width 57.1 mm
Height 75.5 mm
Depth 63 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Nominal voltage UN 250 V AC/DC
Max. current carrying capacity per branch 15 A
Total current 30 A (per potential)
Potential connections Per potential (P1, P2) 2 power/12 distributor terminal blocks
Mounting position any
Standards/regulations IEC 60664
DIN EN 50178
Degree of pollution 2
Overvoltage category III
Connection data, supply
Connection method Push-in-/Spring-cage connection
Stripping length 15 mm
Conductor cross section solid 0.25 mm² ... 6 mm²
Conductor cross section flexible 0.25 mm² ... 4 mm²
Conductor cross section AWG 24 ... 10
Number of connections 2
Connection data, distribution
Connection method Push-in connection
Stripping length 8 mm
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 26 ... 14
Number of connections 24
Standards and Regulations
Connection in acc. with standard CSA
Standards/regulations IEC 60664
DIN EN 50178
Degree of pollution 2
Overvoltage category III
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/PT/PDM-2/24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.