INDUSTRIAL COMPONENT DATA

VIP-3/PT/D25SUB/M/LED 2904260 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/PT/D25SUB/M/LED



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-3/PT/D25SUB/M/LED
Catalog number	2904260
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-32BC188B20
Generated	2026-11-18

Product Overview

Interface module
VARIOFACE module, with push-in connections and D-SUB miniature male connector, for mounting on NS 35 symmetrical rails, with LED, number of poles: 25

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2904260
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 573 (C-5-2017)
GTIN 4046356813372
Weight per Piece (excluding packing) 154.200 g
Custom tariff number 85366990
Country of origin US (United States)
Dimensions
Width 57.1 mm
Height 75.8 mm
Depth 63 mm

Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 24 V DC
Max. perm. current (per branch) 2 A
Number of positions 25
Status display LED
Mounting position any
Connection data for connection 1
Connection name Field level
Connection method Push-in connection
Stripping length 8 mm
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 26 ... 14
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 25
Standards and Regulations
Connection in acc. with standard CSA
Standards/regulations IEC 60664
DIN EN 50178
Rated surge voltage 1.2 kV
Degree of pollution 2
Overvoltage category II
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/PT/D25SUB/M/LED with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.