INDUSTRIAL COMPONENT DATA

VIP-3/PT/HD44SUB/F 2904274 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-3/PT/HD44SUB/F



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-3/PT/HD44SUB/F
Catalog number	2904274
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-BF35845D7D
Generated	2026-11-19

Product Overview

Interface module
VARIOFACE module, with push-in and high-density D-SUB miniature connection sockets, for mounting on symmetrical NS 35 rails, number of poles: 44

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2904274
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 576 (C-5-2017)
GTIN 4046356814836
Weight per Piece (excluding packing) 203.800 g
Custom tariff number 85366990
Country of origin US (United States)
Dimensions
Width 82.5 mm
Height 75.8 mm
Depth 63 mm

Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
60 V DC
Max. perm. current (per branch) 1 A
Number of positions 44
Status display No
Mounting position any
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Number of positions 26
Connection data for connection 2
Connection name Controller level
Connection method High-density D-SUB socket strip
Number of connections 1
Number of positions 44
Standards and Regulations
Connection in acc. with standard CSA
Standards/regulations EN 50178
Rated surge voltage 1.2 kV
Degree of pollution 2
Overvoltage category II
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classification...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-3/PT/HD44SUB/F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.