INDUSTRIAL COMPONENT DATA

# UM 25-D15SUB/S/FRONT/Q 2959599 PHOENIX CONTACT Interface module

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UM 25-D15SUB/S/FRONT/Q**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UM 25-D15SUB/S/FRONT/Q |
| Catalog number | 2959599 |
| Category | Interface module |
| Minimum order | 1 Pcs |
| Document ID | EO-42FA1A08B7 |
| Generated | 2026-11-19 |

## Product Overview

Interface module
VARIOFACE SLIM-LINE, with screw connection and subminiature male connector D, for cross-mounting on NS 35/7.5, number of poles 15

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Key Commercial Data
Orderkey 2959599
Packing unit 1 pc
Catalog page Page 574 (C-5-2017)
GTIN 4017918086244
Weight per Piece (excluding packing) 109.070 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 25 mm
Height 147 mm
Depth 45 mm
Ambient conditions

Ambient temperature (operation) -10 °C ... 50 °C
Ambient temperature (storage/transport) -10 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
60 V DC
Max. perm. current (per branch) 2.5 A
1.5 A (with even load on all branches)
Number of positions 15
Mounting position any
Degree of protection IP20
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 15
Standards and Regulations
Standards/regulations DIN EN 50178
IEC 60664
Rated insulation voltage 125 V
Rated surge voltage 1.2 kV (Functional insulation)
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.02...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM 25-D15SUB/S/FRONT/Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.