INDUSTRIAL COMPONENT DATA

VBST 4-FS/FS(8-2,8-0,8) 0851013 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: VBST 4-FS/FS(8-2,8-0,8)



Manufacturer	PHOENIX CONTACT
MPN / Reference	VBST 4-FS/FS(8-2,8-0,8)
Catalog number	0851013
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-3C3377B76F
Generated	2026-11-18

Product Overview

Feed-through terminal block
Feed-through, connection type: Flat plug connection, cross-section: 0.2 mm² - 4 mm², AWG: 24 - 14, width: 6.2 mm, colour: grey, mounting: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 0851013
Packing unit 50 pc
Note Made to Order (non-returnable)
GTIN 4017918007973
Weight per Piece (excluding packing) 8.000 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 2
Number of connections 8
Nominal cross section 2.5 mm²
Color gray

Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection method Slip-on connection
Maximum load current 32 A (with 4 mm² conductor cross section)
Nominal current IN 24 A
Nominal voltage UN 800 V
Open side panel Yes
Dimensions
Width 6.2 mm
Length 72 mm
Height NS 35/7,5 39.5 mm
Height NS 35/15 47 mm
End cover width 2.2 mm
Connection data
Connection method Slip-on connection
Screw thread M3
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 24
Max. AWG conductor cross section, flexible 14
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VBST 4-FS/FS(8-2,8-0,8) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.