INDUSTRIAL COMPONENT DATA

FBS-PV UT 3047358 PHOENIX CONTACT Potential bridge

Brand: PHOENIX CONTACT | Manufacturer Part Number: FBS-PV UT



Manufacturer	PHOENIX CONTACT
MPN / Reference	FBS-PV UT
Catalog number	3047358
Category	Cross-connector for terminal block
Minimum order	50 Pcs
Document ID	EO-BE765C95AC
Generated	2026-11-18

Product Overview

Potential bridge
Vertical potential bridge, for connecting the upper and lower floors
Vertical potential bridge, to connect the upper and lower level

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Vertical bridge
Number of positions 1
Data management status
Article revision 03
Electrical propertiesMaximum load current 22 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
Connection dataMaximum load current 22 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
DimensionsWidth 5.2 mm
Height 3 mm
Depth 44 mm
Length 3 mm
Material specificationsColor black (RAL 9005)

Material Copper
Flammability rating according to UL 94 V0
Insulating material PA
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (operation) 20 % ... 90 %
Permissible humidity (storage/transport) 30 % ... 70 %
MountingMounting type Plug-in mounting

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBS-PV UT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.