INDUSTRIAL COMPONENT DATA

VIP-2/PT/D37SUB/M/ET200SP-HA 1100964 PHOENIX CONTACT VARIOFACE module for the SIMATIC ET200SP HA with push-i..

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/PT/D37SUB/M/ET200SP-HA



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/PT/D37SUB/M/ET200SP-HA
Catalog number	1100964
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-62A79B8A79
Generated	2026-11-19

Product Overview

VARIOFACE module for the SIMATIC ET200SP HA with push-in connections and male D-SUB connector, for mounting on NS 35 rails, 37-pos.
VARIOFACE module for SIMATIC ET200SP HA with push-in connections and D-SUB connector, for installation on DIN NS 35 rails, number of poles: 37

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 1100964
Packing unit 1 pc
GTIN 4055626956541
Weight per Piece (excluding packing) 200.000 g
Custom tariff number 85369010
Country of origin US (United States)
Drawings
Dimensions
General

Connection data 2
Standards and Regulations
Classifications
Note
Ambient conditions
Connection data
Supported controller
Environmental Product Compliance
Drawings
Circuit diagram
Back to topNote
Note Standard or halogen-free cables
Back to topDimensions
Width 102.8 mm
Height 72.1 mm
Depth 46.6 mm
Back to topAmbient conditions
Ambient temperature (operation) -20 °C ... 70 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Back to topGeneral
Nominal voltage UN 25 V AC
60 V DC
Max. perm. current (per branch) 2 A
Number of positions 37
Status display No
Mounting position any
Back to topConnection data
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Push-in connection
Stripping length 8 mm
Number of positions 37
Conductor cross section solid 0.14 mm² ... 4 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
Conductor cross section AWG 26 ... 14
Back to topConnection data 2
Connection name Controller level
Connection method D-SUB pin strip
Number of connections 1
Number of positions 37
Back to topSupported controller
Controller SIEMENS ET200SP HA
- suitable I/O card 6DL1131-6BH00-0PH1
6DL1131-6TH00-0PH1
6DL1131-6BL00-0PH1
6DL1132-6BH00-0PH1
6DL1132-6BL00-0PH1

6DL1134-6TH00-0PH1
6DL1134-6JH00-0PH1
6DL1135-6TF00-0PH1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/PT/D37SUB/M/ET200SP-HA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.