INDUSTRIAL COMPONENT DATA

VIP-2/SC/FLK16/ISP 4AI 2DMU 2903869 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-2/SC/FLK16/ISP 4AI 2DMU



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-2/SC/FLK16/ISP 4AI 2DMU
Catalog number	2903869
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-1D394BE811
Generated	2026-11-18

Product Overview

Passive module
VARIOFACE Professional (VIP) module for Siemens ET200 ISP control systems. HART interface with analog input, 4 channels. 125 V AC/DC, rating 1 A, bipolar.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2903869
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356827546
Weight per Piece (excluding packing) 333.330 g
Custom tariff number 85366990
Country of origin US (United States)
Dimensions
Width 45 mm
Height 65.5 mm
Depth 56 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 60 V AC/DC
Max. perm. current (per branch) 1 A
Number of positions 16
Status display No
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M 3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method IDC/FLK pin strip
Number of connections 1
Number of positions 16
Pitch 2.54 mm
Supported controller
Controller Siemens ET200 ISP
- suitable I/O card 6ES7134-7TD00-0AB0
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127250300eCl@ss 6.027242600eCl@ss 7.027141152eCl@...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-2/SC/FLK16/ISP 4AI 2DMU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.