INDUSTRIAL COMPONENT DATA

VIP-PA-FLK14/ 3,0M/S7 2322702 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-PA-FLK14/ 3,0M/S7



Manufacturer	PHOENIX CONTACT
MPN / Reference	VIP-PA-FLK14/ 3,0M/S7
Catalog number	2322702
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-17187325B1
Generated	2026-11-18

Product Overview

Front adapters
VIP VARIOFACE front adapter, with system cables connected for SMATIC S7-300, connectable 2 x 8 channels, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2322702
Packing unit 1 pc
Catalog page Page 501 (C-5-2017)
GTIN 4046356452465
Weight per Piece (excluding packing) 573.900 g
Custom tariff number 85444290
Country of origin DE (Germany)
Note
Type of note Notes on operation
Note Analog I/O cards
To avoid short-circuits, all wire bridges must be disconnected!
No voltage supply may be supplied to the front adapter!

Type of note Notes on operation
Note Digital I/O cards
Thanks to the existing wire bridge upon delivery, the input and output bytes are non-isolated.
General
Max. permissible operating voltage < 50 V AC
60 V DC
Max. permissible current 1 A (per path)
8 A (Separate power supply)
Mounting position any
Degree of protection IP20
Connection data 1
Connection name Control side
Connection method Plug connection
Note Can be plugged onto 20-pos. I/O modules
Connection data 2
Connection name Field level
Connection method IDC/FLK socket strip
Number of connections 2
Number of positions 14
Pitch 2.54 mm
Connection data 3
Connection name Supply
Connection method Push-in connection
Stripping length 10 mm
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 14
Cable
Conductor construction: Number of litz wires: 7
Single wire, material Cu tin-plated
Single wire, cross section 0.14 mm²
External diameter 6.4 mm
Length of cable 3 m
Shielding no
Halogen-free cable No
Max. conductor resistance 0.16 ?/m
Supported controller
Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-PA-FLK14/ 3,0M/S7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.