INDUSTRIAL COMPONENT DATA

# VIP-PA-4X14/26/ 2,0M/1756/040 1162499 PHOENIX CONTACT VARIOFACE VIP front adapter, with connected system cab..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VIP-PA-4X14/26/ 2,0M/1756/040**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VIP-PA-4X14/26/ 2,0M/1756/040 |
| Catalog number | 1162499 |
| Category | Accessories/spare parts for controls |
| Minimum order | 1 Pcs |
| Document ID | EO-BF5787383C |
| Generated | 2026-11-19 |

## Product Overview

VARIOFACE VIP front adapter, with connected system cables for ControlLogix 1756 I/O module, connectable up to 4 x 8 channels.
VIP VARIOFACE front adapter, with connected system cables for ControlLogix® 1756 I/O. Up to 4 x 8 channels can be connected., cable length: 2 m

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Technical dataProduct propertiesProduct type Front adapter
Product family VARIOFACE Professional
Insulation characteristics
Overvoltage category II
Pollution degree 2
Electrical propertiesMax. permissible operating voltage 60 V DC
Max. permissible current 1 A (per path)
6 A (per group, positive terminals)
8 A (per group, negative terminals)
Supported controller ALLEN-BRADLEY ControlLogix
Suitable I/O card 1756-IB32
Connection dataCross section AWG (converted acc. to IEC)

Controller level
Connection method Plug-in connection
Note Can be plugged onto 36-pos. I/O modules
Field level
Connection in acc. with standard IEC 60603-13
Connection method IDC/FLK socket strip
Number of connections 4
Number of positions 14
Pitch 2.54 mm
Supply
Connection method Push-in / plug connection
Stripping length 9 mm
Conductor cross section rigid 0.14 mm² ... 1.5 mm²
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section AWG 26 ... 16
DimensionsItem dimensions
Width 344.943 mm
Height 47.352 mm
Depth 56.345 mm
Cable
Length 2 m
Cable/line14X0.14 [PVC]
UL AWM Style 2464/1061
Number of positions 14
Shielded no
Cable type 14X0.14 [PVC]
Conductor type Round cable set
Conductor structure signal line 7x 0.16 mm
AWG signal line 26
Conductor cross section 14x 0.14 mm²
Wire diameter incl. insulation 1 mm ±0.03 mm
External cable diameter 6.4 mm ±0.4 mm
Outer sheath, material Semi-rigid PVC
External sheath, color gray
Conductor material Tin-plated Cu litz wires
Cable resistance <= 145 ?/k...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VIP-PA-4X14/26/ 2,0M/1756/040 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.