INDUSTRIAL COMPONENT DATA

VS-04-2X2X26C7/7-67A/SDB/0,5 1657685 PHOENIX CONTACT Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-04-2X2X26C7/7-67A/SDB/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-04-2X2X26C7/7-67A/SDB/0,5
Catalog number	1657685
Category	Pigtail
Minimum order	1 Pcs
Document ID	EO-9AB1231B70
Generated	2026-11-18

Product Overview

Patch cable
Ready-made USB cable, shielded, colour: RAL 5021 (aqua blue), PUR outer wrap, USB Type-A/IP67 to USB Type-B/standard, length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1657685
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356118507
Weight per Piece (excluding packing) 75.500 g
Custom tariff number 85444290
Country of origin DE (Germany)
Ambient conditions
Degree of protection IP20
IP67
Ambient temperature (operation) -20 °C ... 60 °C (cable, fixed installation)
0 °C ... 50 °C (cable, flexible installation)

Plug / socket
General data
Number of positions 4
Degree of pollution 2
Alternative short product description USB cable
Rated voltage (III/3) 125 V
Housing material PA
Cable
Cable type FireWire
Cable type (abbreviation) 980
Signal type/category USB CAT7, 480 Mbps
FireWire CAT7, 400 Mbps
Cable structure 2x2xAWG26/7 + 2xAWG20/19; S/FTP
Conductor cross section 2x 2x 0.14 mm² (Signal line)
2x 0.5 mm² (Power supply)
AWG signal line 26
AWG power supply 20
Conductor structure signal line 7x 0.15 mm
Conductor structure, voltage supply 19x 0.20 mm
Core diameter including insulation <= 1.05 mm (Signal line)
nom. 1.4 mm (Power supply)
Wire colors White-blue, white-orange, white, black
Twisted pairs 2 cores to the pair
Type of pair shielding Aluminum-lined polyester foil
Overall twist Two pairs and two power supply wires to the core
Shielding Tinned copper braided shield
External sheath, color water blue RAL 5021
External cable diameter D 6.7 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 5 x D
Tensile strength GRP <= 30 N
Cable weight 59 kg/km
Outer sheath...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-04-2X2X26C7/7-67A/SDB/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.