INDUSTRIAL COMPONENT DATA

VS-M12FSBP-M12MS-936-LI/1,55 1403383 PHOENIX CONTACT Netzwerkkabel

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-M12FSBP-M12MS-936-LI/1,55



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-M12FSBP-M12MS-936-LI/1,55
Catalog number	1403383
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2DF55CEFEE
Generated	2026-11-19

Product Overview

Netzwerkkabel
Conect. plug. to be apar. poster wall, PROFINET CAT5 (100 MBit/s), 4-pole, PE-X, black RAL 9005, shielded, Straight connector M12, coding: D SPEEDCON / IP67, a Straight built-in mounting female M12, coding: D / IP67, cable length: 1.55 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1403383
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356650168
Weight per Piece (excluding packing) 164.400 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 1.55 m
Ambient conditions

Degree of protection IP65
IP67
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
-40 °C ... 90 °C (cable, fixed installation)
-25 °C ... 90 °C (cable, flexible installation)
General data
Rated current at 40°C 4 A
Rated voltage 250 V
Number of positions 4
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
Standards/regulations M12 connector IEC 61076-2-101
Overvoltage category II
Characteristics head 1
Head type Plug straight M12 SPEEDCON / IP67
No. of positions (pin connector pattern) 4
Coding D (Data)
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Insulation resistance >= 100 M?
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Ambient temperature (operation) -25 °C ... 90 °C
Characteristics head 2
Head type Flush-type socket straight M12 / IP67
No. of positions (pin connector pattern) 4
Coding D (Data)
Material (component) CuZn (Contact)
Ni/Au (Contact surface)
PA 6.6 (Contact carriers)
FKM (O-ring)
Zinc die-cast, nickel-plated (Housing)
Insertion/withdrawal cycles >= 100
Ambient temperature (operation) -40 °C ... 85 °C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-M12FSBP-M12MS-936-LI/1,55 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.