INDUSTRIAL COMPONENT DATA

VS-M12MSD-IP20-LI-93P/10,0 1445279 PHOENIX CONTACT Assembled Ethernet cable, CAT5e, shielded, 2-pair, 26 AWG..

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-M12MSD-IP20-LI-93P/10,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-M12MSD-IP20-LI-93P/10,0
Catalog number	1445279
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-F0DD19D7D7
Generated	2026-11-19

Product Overview

Assembled Ethernet cable, CAT5e, shielded, 2-pair, 26 AWG stranded (7-wire), RAL 5021 (water blue), M12 plug to RJ45 plug/IP20, line, length: 10 m
Ready-made Ethernet cable, CAT5e, shielded, 2-pair, flexible AWG 26 (7-wire), RAL 5021 (water blue), male connector M12 to male connector RJ45/IP20, line, length 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1445279
Packing unit 1
GTIN 4046356582643
Custom tariff number 85444290
Drawings
Ambient conditions
Standards and Regulations
Classifications
Dimensions
General data
Environmental Product Compliance

Drawings
Dimensional drawing
Plug, M12 x 1, straight, shielded
Dimensional drawing
RJ45 connector, IP20
Back to topDimensions
Length of cable 10 m
Back to topAmbient conditions
Ambient temperature (operation) -25 °C ... 60 °C (cable, fixed installation)
-5 °C ... 50 °C (cable, flexible installation)
Back to topGeneral data
Rated voltage 48 V AC
60 V DC
Number of positions 4
Signal type/category Ethernet CAT5 (IEC 11801:2002)
Degree of pollution 3
Alternative short product description Ethernet cable
Back to topStandards and Regulations
Flammability rating according to UL 94 V2
Back to topEnvironmental Product Compliance
REACh SVHC
Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Back to topClassifications
eCl@ss
eCl@ss 4.0 27060300
eCl@ss 4.1 27060300
eCl@ss 5.0 27060300
eCl@ss 5.1 27060300
eCl@ss 6.0 27279200
eCl@ss 7.0 27279218
eCl@ss 8.0 27279218
eCl@ss 9.0 27060311
Back to topETIM
ETIM 3.0 EC000830
ETIM 4.0 EC000830
ETIM 5.0 EC001855
ETIM 6.0 EC001855
ETIM 7.0 EC001855
Back to topUNSPSC
UNSPSC 6.01 31261501
UNSPSC 7.0901 31261501
UNSPSC 11 31261501
UNSPSC 12.01 31261501
UNSPSC 13.2 31251501
UNSPSC 19.0 31251501

UNSPSC 20.0 31251501....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-M12MSD-IP20-LI-93P/10,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.