INDUSTRIAL COMPONENT DATA

VS-MSD-MSD-93B-LI/10,0 1404309 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-MSD-MSD-93B-LI/10,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-MSD-MSD-93B-LI/10,0
Catalog number	1404309
Category	Patch cord copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-1A2F3E9ADC
Generated	2026-11-19

Product Overview

Network cable
Ready-made PROFINET cable, CAT 5e, shielded, star quads, flexible AWG 22 (7 wires), RAL 6018 (yellow green), M12 to M12 connector, Line, length 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1404309
Packing unit 1
GTIN 4046356690157
Custom tariff number 85444210
Mechanical characteristics
Number of positions 4
Insertion/withdrawal cycles >= 100
Length of cable 10 m
Degree of protection IP65/IP67/IP69K
No. of cable outlets 1
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C (cable, fixed installation)

-5 °C ... 50 °C (cable, flexible installation)
Material data
Flammability rating according to UL 94 V0
Electrical characteristics
Transmission characteristics (category) CAT5 (IEC 11801:2002)
Standards and Regulations
Flammability rating according to UL 94 V0
Line characteristics
Cable type PROFINET PVC stranded CAT5
Cable abbreviation 2YY(ST)CY
UL AWM style 21694
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.55 mm
External cable diameter 6.5 mm ±0.2 mm
Wire colors White, yellow, blue, orange
External sheath, color green RAL 6018
Transmission medium Copper
Insulation resistance >= 500 M?*km
Wave impedance 100 ? ±15 ? (at 100 MHz)
Near end crosstalk attenuation (NEXT) 80 dB (with 1 MHz)
76 dB (at 4 ?Hz)
70 dB (at 10 MHz)
65 dB (at 16 MHz)
63 dB (at 20 ?Hz)
60 dB (at 31.25 ?Hz)
55 dB (at 62.5 ?Hz)
50 dB (at 100 MHz)
Wave attenuation 2.1 dB (with 1 MHz)
4 dB (at 4 ?Hz)
6.3 dB (at 10 MHz)
8 dB (at 16 MHz)
9 dB (at 20 ?Hz)
11.4 dB (at 31.25 ?Hz)
16.5 dB (at 62.5 ?Hz)
21.3 dB (at 100 MHz)
Signal speed 0.66...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-MSD-MSD-93B-LI/10,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.