INDUSTRIAL COMPONENT DATA

VS-OE-OE-925-100,0 1402838 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-OE-OE-925-100,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-OE-OE-925-100,0
Catalog number	1402838
Category	Data cable
Minimum order	1 Pcs
Document ID	EO-632A75E223
Generated	2026-11-19

Product Overview

Bus system cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1402838
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356632546
Weight per Piece (excluding packing) 6,380.000 g
Custom tariff number 85444995
Country of origin DE (Germany)
Dimensions
Length of cable 100 m
General data
Number of positions 4
Signal type/category DeviceNet™
Cable
Cable type DeviceNet™

Cable type (abbreviation) 925
Signal type/category DeviceNet™
Cable structure 2xAWG24/19+2xAWG22/19
Conductor cross section 2x 0.25 mm² (Signal line)
2x 0.34 mm² (Power supply)
AWG signal line 24
AWG power supply 22
Conductor structure signal line 19x 0.12 mm
Conductor structure, voltage supply 19x 0.15 mm
Wire colors Red-black, blue-white
Twisted pairs 2 cores to the pair
Type of pair shielding Aluminum-lined polyester foil
Overall twist 2 pairs and one drain wire to the core
Shielding Tinned copper braided shield
External sheath, color violet RAL 4001
External cable diameter D 6.9 mm ±0,3 mm
Smallest bending radius, fixed installation 110 mm
Cable weight 70 kg/km
Outer sheath, material FRNC
Material conductor insulation Cell PE
Conductor material Tin-plated Cu litz wires
Insulation resistance >= 0.2 G?*km
Conductor resistance <= 90 ?/km
Working capacitance 39.8 nF
Wave impedance 120 ? ±10 %
Shield attenuation < 0.95 dB (At 125 kHz)
< 1.64 dB (At 500 kHz)
Test voltage, cable 2000 V
Ambient temperature (operation) -25 °C ... 80 °C (cable, fixed installation)
Environmental Product Compliance
China RoHS Environmentally Friendly Use Perio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-OE-OE-925-100,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.