INDUSTRIAL COMPONENT DATA

VS-PPC-F1-RJ45-POBK-1RF-BU/BU 1404760 PHOENIX CONTACT Panel mounting frames

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-F1-RJ45-POBK-1RF-BU/BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC-F1-RJ45-POBK-1RF-BU/BU
Catalog number	1404760
Category	Fixing element for industrial connectors
Minimum order	1 Pcs
Document ID	EO-883580FB0D
Generated	2026-11-18

Product Overview

Panel mounting frames
Recessed frame RJ45, IP54, for push-pull lock, for rectangular mounting opening, with gasket, without fixing screws, plastic, with RJ45 contact insert, 8 poles, shielded, female connector to female connector, CAT5e, Freenet system

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1404760
Packing unit 1 pc
GTIN 4046356320849
Weight per Piece (excluding packing) 19.800 g
Custom tariff number 85366990
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 8
Shielded yes
Insertion/withdrawal cycles >= 500
Color black
Insulation resistance >= 500 M?

Degree of protection IP67
Type RJ45, IP65/67, version 14
Ambient conditions
Ambient temperature (operation) -20 °C ... 70 °C
Ambient temperature (assembly) -10 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
Material data
Flammability rating according to UL 94 V0
Housing material PA-GF
Contact carrier material Thermoplastic
Contact material Copper alloy
Contact surface material Gold over nickel
Sealing material NBR
Seal material NBR
Height 42 mm
Electrical characteristics
Number of positions 8
Transmission characteristics (category) CAT5 (IEC 11801:2002)
GRP transmission properties CAT5 (IEC 11801:2002)
Rated current 1 A
Overvoltage category I
Degree of pollution 1
Rated voltage (III/3) 72 V (DC)
72 V (DC)
Rated surge voltage >= 1 kV
Rated current 1 A
Insulation resistance >= 500 M?
Transmission characteristics (category) CAT5 (IEC 11801:2002)
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-F1-RJ45-POBK-1RF-BU/BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.