INDUSTRIAL COMPONENT DATA

WST 6 3030967 PHOENIX CONTACT Warning cover

Brand: PHOENIX CONTACT | Manufacturer Part Number: WST 6



Manufacturer	PHOENIX CONTACT
MPN / Reference	WST 6
Catalog number	3030967
Category	Warning/signing plate
Minimum order	10 Pcs
Document ID	EO-0CAD86E21E
Generated	2026-11-18

Product Overview

Warning cover
Warning cover, Strips, yellow, labeled, mounting type: plugged in, for terminal width: 8.2 mm, usable area: 10.4 x 7.55 mm, Number of individual indexes: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 3030967
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 163 (C-3-2017)
GTIN 4017918193126
Weight per Piece (excluding packing) 0.770 g
Custom tariff number 49119900
Country of origin PL (Poland)
Dimensions
Length (b) 10.4 mm
Width (a) 8.2 mm
Height (c) 1 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C
General
Color yellow
Type high
Components free from silicone and halogen
Flammability rating according to UL 94 V2
Material PA
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 5
Number of individual labels per row 5
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Plug in
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94 V2
Classifications
eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027141145eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141137eCl@ss 8.027141...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WST 6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.