INDUSTRIAL COMPONENT DATA

PML-W200 (50X50)R CUS 0830497 PHOENIX CONTACT Warning label

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-W200 (50X50)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-W200 (50X50)R CUS
Catalog number	0830497
Category	Warning/signing plate
Minimum order	1 Pcs
Document ID	EO-291FE60BF7
Generated	2026-11-19

Product Overview

Warning label
Warning plate, available: by lines, yellow/black, labelled according to customer specifications: White, mounting type: glued, diameter: 0 mm, usable area: 50 x 50 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0830497
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 321 (C-5-2013)
GTIN 4046356718097
Weight per Piece (excluding packing) 1.990 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 50 mm
Width (a) 50 mm
Height (c) 59.25 mm

Diameter 0.00 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C
Ambient temperature (assembly) > 8 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color yellow/black
Type Triangle
Components Silicone-free
Material PVC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing Blank
Number of individual labels 500
Number of individual labels per row 1
Adhesive Acrylic
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Marking mounting type adhesive
Standards and Regulation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-W200 (50X50)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.