INDUSTRIAL COMPONENT DATA

PML-W101 (12,5X12,5) 0830432 PHOENIX CONTACT Warning label

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-W101 (12,5X12,5)



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-W101 (12,5X12,5)
Catalog number	0830432
Category	Warning/signing plate
Minimum order	5 Pcs
Document ID	EO-283FADA315
Generated	2026-11-18

Product Overview

Warning label
Warning plate, Elbow, yellow/black, labeled: Lightning with arrow, mounting type: glued, diameter: 0 mm, usable area: 12.5x12.5mm, Number of individual indexes: 110

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0830432
Packing unit 5 pc
Minimum order quantity 5 pc
Note Made to Order (non-returnable)
Catalog page Page 105 (NTK-2012)
GTIN 4046356717564
Weight per Piece (excluding packing) 5.840 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Length (b) 12.5 mm
Width (a) 12.5 mm

Height (c) 10.83 mm
Diameter 0.00 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C
Ambient temperature (assembly) > 8 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color yellow/black
Type Triangle
Components Silicone-free
Material PVC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing Lightning flash
Number of individual labels 110
Number of individual labels per row 11
Adhesive Acrylic
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Environmental Product Compliance
REACh SVHC Reaction mass of DOT...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-W101 (12,5X12,5) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.