INDUSTRIAL COMPONENT DATA

PML-W301 (74X37) 0830462 PHOENIX CONTACT Warning label

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-W301 (74X37)



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-W301 (74X37)
Catalog number	0830462
Category	Warning/signing plate
Minimum order	5 Pcs
Document ID	EO-D75C99C311
Generated	2026-11-18

Product Overview

Warning label
Warning plate, Elbow, yellow/black, labeled: Lightning with arrow and warning in German, English, mounting class: glued, diameter: 0 mm, usable surface: 74 x 37 mm, Number of individual indices: 3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0830462
Packing unit 5 pc
Minimum order quantity 5 pc
Note Made to Order (non-returnable)
Catalog page Page 371 (C-3-2017)
GTIN 4046356717861
Weight per Piece (excluding packing) 5.940 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Length (b) 37 mm
Width (a) 74 mm

Height (c) 37 mm
Diameter 0.00 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color yellow/black
Type Rectangle
Components Silicone-free
Material PVC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing Lightning flash and warning in German, English
Number of individual labels 3
Number of individual labels per row 1
Adhesive Acrylic
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Environmental Product Compliance
REACh SVHC Reaction mass of DOTE and MOTE
Class...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-W301 (74X37) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.