INDUSTRIAL COMPONENT DATA

WML 7,5 (17X9)RL 1110065 PHOENIX CONTACT Cable marker label, Roll, white, unlabeled, can be labeled with: TH..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 7,5 (17X9)RL



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 7,5 (17X9)RL
Catalog number	1110065
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-45CCFA4CCB
Generated	2026-11-18

Product Overview

Cable marker label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK S1.1, mounting type: adhesive, cable diameter: <= 7.5 mm, lettering field size: 17 x 9 mm, Number of individual labels: 5000
Cable wrapping label, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, cable diameter range: 2.9 ... 7.6 mm, cable diameter: <= 7.6 mm, usable area: 17x9mm, Number of individual indexes: 5000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 1110065
Packing unit 1 pc
GTIN 4063151024437
Weight per Piece (excluding packing) 820.000 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
General

Classifications
Ambient conditions
Standards and Regulations
Dimensions
Length (b) 35 mm
Width (a) 17 mm
Back to topAmbient conditions
Ambient temperature (operation) -50 °C ... 110 °C
Recommended storage conditions 23 °C / 50% relative humidity. Storage in poly bags is recommended prior to processing.
Back to topGeneral
Color white
Base element material Vinyl film
Type Label
Components Silicone-free
Material PVC
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 5000
Number of individual labels per row 4
Adhesive Acrylic
Printability Thermal transfer
Device 1085260 THERMOMARK ROLL 2.0
0804501 THERMOMARK ROLLMASTER 300
0804663 THERMOMARK ROLLMASTER 600
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Result of weather resistance test Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result of wipe resistance test Test passed
Foil strength 50 µm
Adhesive strength 25 µm
Marking mounting type adhesive
Back to topSta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 7,5 (17X9)RL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.